


Coupling Link G

For use with Grade 100 or Grade 80 chain. For use with master link and eye hook.




| Stock No. | Code | WLL (lb) | L | B | F | A | C | Weight (lb) |
|-----------|---------|----------|------|------|------|------|------|-------------|
| Z100821 | G-6-10 | 3306 | 1.77 | 0.59 | 0.28 | 0.31 | 0.63 | 0.22 |
| Z101358 | G-7-10 | 4500 | 2.20 | 0.71 | 0.35 | 0.43 | 0.87 | 0.44 |
| Z100822 | G-8-10 | 5700 | 2.20 | 0.71 | 0.35 | 0.43 | 0.87 | 0.44 |
| Z100823 | G-10-10 | 8800 | 2.68 | 0.98 | 0.47 | 0.51 | 1.02 | 0.66 |
| Z100824 | G-13-10 | 15000 | 3.50 | 1.14 | 0.59 | 0.67 | 1.30 | 1.54 |
| Z100825 | G-16-10 | 22600 | 4.17 | 1.42 | 0.75 | 0.79 | 1.57 | 3.09 |
| Z101119 | G-20-10 | 35300 | 4.92 | 1.69 | 0.91 | 1.02 | 1.73 | 4.85 |
| Z101339 | G-22-10 | 44080 | 5.98 | 1.97 | 1.02 | 1.10 | 2.32 | 7.72 |
| Z101365 | G-26-10 | 60169 | 6.34 | 2.28 | 1.26 | 1.34 | 2.40 | 12.57 |
| Z101666 | G-32-10 | 88160 | 7.87 | 2.76 | 1.50 | 1.57 | 3.03 | 20.94 |

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M-02 and AS 3776:2015.

Grab Hook GG

Clevis shortening hook. For use with Grade 100 or Grade 80 chain. No reduction of working load limit, thanks to supporting cradle lugs on either side of hook to prevent chain link deformation.




| Stock No. | Code | WLL (lb) | L | B | Weight (lb) |
|-----------|----------|----------|------|------|-------------|
| Z101844 | GG-6-10 | 3306 | 2.13 | 0.31 | 0.44 |
| Z100845 | GG-7-10 | 4500 | 2.24 | 0.39 | 0.66 |
| B14771 | GG-8-10 | 5700 | 2.24 | 0.39 | 0.88 |
| B14772 | GG-10-10 | 8800 | 2.99 | 0.47 | 1.98 |
| B14773 | GG-13-10 | 15000 | 3.82 | 0.63 | 3.97 |
| B14774 | GG-16-10 | 22600 | 4.49 | 0.79 | 6.83 |
| Z101152 | GG-20-10 | 35300 | 5.79 | 1.02 | 15.43 |

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Grab Hook GG with Locking Pin

Clevis shortening hook with locking pin for extra safety. For use with Grade 100 or Grade 80 chain. No reduction of working load limit, thanks to supporting cradle lugs on either side of hook to prevent chain link deformation.




| Stock No. | Code | WLL (lb) | L | B | Weight (lb) |
|-----------|-------------|----------|------|------|-------------|
| B14971 | GG-8-10 LP | 5700 | 2.24 | 0.39 | 0.88 |
| B14972 | GG-10-10 LP | 8800 | 3.03 | 0.47 | 1.98 |
| B14973 | GG-13-10 LP | 15000 | 3.82 | 0.63 | 4.19 |
| B14974 | GG-16-10 LP | 22600 | 4.49 | 0.79 | 7.05 |

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.

Grab Hook OG

Eye shortening hook. For use with Grade 100 or Grade 80 chain. No reduction of working load limit, thanks to supporting lugs on either side of hook to prevent chain link deformation.



| Stock No. | Code | WLL (lb) | L | B | E | F | Weight (lb) |
|-----------|-----------|----------|------|------|------|------|-------------|
| Z101296 | OG-7/8-10 | 5700 | 2.56 | 0.39 | 0.67 | 0.39 | 0.66 |
| Z101297 | OG-10-10 | 8800 | 3.35 | 0.47 | 0.79 | 0.47 | 1.54 |
| Z101298 | OG-13-10 | 15000 | 4.09 | 0.63 | 1.02 | 0.63 | 3.53 |
| Z101299 | OG-16-10 | 22600 | 5.16 | 0.79 | 1.26 | 0.75 | 6.17 |
| Z101300 | OG-20-10 | 35300 | 6.57 | 1.02 | 1.61 | 0.91 | 13.45 |
| Z101301 | OG-22-10 | 44094 | 7.36 | 1.02 | 1.81 | 1.26 | 18.96 |
| Z101302 | OG-26-10 | 60169 | 8.98 | 1.26 | 2.17 | 1.50 | 30.86 |
| Z101303 | OG-32-10 | 88160 | 9.02 | 1.57 | 1.97 | 1.06 | 45.64 |

4:1 Design Factor. Fulfills requirements in: EN 1677:2008 (WLL +25%), ASTM A952/A952M and AS 3776:2015.